

JWL DOT E



FULLY COMPLIANT WITH ISO, JWL, DOT E AND TÜV



GP TEK Front Wheel Facts



Size

3.50" x 17"
3.75" x 17"
4.00" x 17"



Weight

1.7 kg complete
depending on fitment



Materials

Wheels: Pre-preg
carbon fiber
Hubs: 6082 T6
Aluminium



Valve Stem

BST Ultra-High-Speed
90° aluminium
stem and cap



Compliance

DOT E and JWL
compliant for street
and track use



Warranty

2 Year Factory
Warranty

Testing




Application

Race wheels



Rotational Inertia

49 000 kg•mm²



Impact Load

325 kg



Torsion Fatigue

908 Nm



Bending Stiffness

1 406 Nm / degree



Bending Fatigue

783 Nm for
1,000,000 cycles



Cornering Frequency

39.0 Hz

JWL DOT E



FULLY COMPLIANT WITH ISO, JWL, DOT E AND TÜV



GP TEK Rear Wheel Facts



Size
6.00" x 17"
6.25" x 17"



Weight
2.5 kg complete
depending on fitment



Materials
Wheels: Pre-preg
carbon fiber
Hubs: 6082 T6
Aluminium



Valve Stem
BST Ultra-High-Speed
90° aluminium
stem and cap



Compliance
DOT E and JWL
compliant for street
and track use



Warranty
2 Year Factory
Warranty


Testing



Application
Race wheels



Rotational Inertia
57 400 kg•mm²



Impact Load
176 kg



Torsion Fatigue
1 043 Nm



Bending Stiffness
1 700 Nm / degree



Bending Fatigue
719 Nm for
1,000,000 cycles



Cornering Frequency
36.3 Hz