

JWL DOT E



FULLY COMPLIANT WITH ISO, JWL, DOT E AND TÜV

Torque TEK Front Wheel Facts



Size
3.5" x 26"
*More sizes available



Weight
4.85 kg complete
depending on fitment



Materials
Wheels: Pre-preg
carbon fiber
Hubs: 6082 T6
Aluminium



Valve Stem
BST Ultra-High-Speed
90° aluminium
stem and cap




Compliance
DOT E and JWL
compliant for street
and track use



Warranty
2 Year Factory
Warranty

Testing



Impact Load
588 kg



Static Load
235 kg



Rotational Inertia
330 000 kg•mm²



Torsion Fatigue
768 Nm



Bending Fatigue
790 Nm for
1,000,000 cycles



Cornering Frequency
37.90 Hz

JWL DOT E



FULLY COMPLIANT WITH ISO, JWL, DOT E AND TÜV



Torque TEK Rear Wheel Facts



Size
5.5" x 18"
*More sizes available



Weight
4.80 kg complete
depending on fitment



Materials
Wheels: Pre-preg
carbon fiber
Hubs: 6082 T6
Aluminium



Valve Stem
BST Ultra-High-Speed
90° aluminium
stem and cap




Compliance
DOT E and JWL
compliant for street
and track use



Warranty
2 Year Factory
Warranty

Testing



Impact Load
615 kg



Static Load
410 kg



Rotational Inertia
158 000 kg•mm²



Torsion Fatigue
1502 Nm



Bending Fatigue
1270 Nm for
1,000,000 cycles



Cornering Frequency
53.3 Hz