



TECHNICAL SPECS

TWIN TEK FRONT WHEEL

SPECS



SIZES

3.5" x 17"
3.5" x 18"
3.0" or 3.5" x 19"
2.15" or 2.5" or 2.75" x 19"
2.15 or 3.5" x 21"



WEIGHT

7.23 lbs / 3.46 kg



MATERIALS

Wheels: Pre-preg carbon fibre
Hubs: 6082 T6 Aluminium



VALVE STEM

BST Ultra-High-Speed 90° aluminium stem and cap



COMPLIANCE

DOT E and JWL compliant for street and track use



WARRANTY

2 Year Factory Warranty

TESTS



RADIAL IMPACT LOAD (JASO T203-85)

1135 lbs / 515 kg (3" x 19")



CORNERING FATIGUE LOAD

805 Nm



STATIC LOAD RATING

567 lbs / 257 kg



TORSION FATIGUE LOAD

708 Nm

FULLY COMPLIANT WITH ISO, JWL, and DOT E



BST.



TECHNICAL SPECS

TWIN TEK CONVENTIONAL REAR WHEEL

SPECS



SIZES

4.5" x 17" 6.0" x 17"
5.5" x 17" 8.0" x 18"
5.5" x 18" 8.5" x 18"



WEIGHT

9.55 lbs / 4.33 kg



MATERIALS

Wheels: Pre-preg carbon fibre
Hubs: 6082 T6 Aluminium



VALVE STEM

BST Ultra-High-Speed 90°
aluminium stem and cap



COMPLIANCE

DOT E and JWL compliant
for street and track use



WARRANTY

2 Year Factory Warranty

TESTS



**RADIAL IMPACT LOAD
(JASO T203-85)**

1 356 lbs / 615 kg (5.5" x 18")



CORNERING FATIGUE LOAD

1 590 Nm



STATIC LOAD RATING

992 lbs / 450 kg



TORSION FATIGUE LOAD

1 277 Nm

FULLY COMPLIANT WITH ISO, JWL, and DOT E

